

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Desktop ESPRIMO Q958

### Mini PC with excellent performance and integration capabilities

The FUJITSU ESPRIMO Q958 mini PC provides excellent performance, high energy efficiency and manageability. Up to 9th Gen Intel® Core™ processor and Intel® vPro™ technology, combined with the DeskView manageability suite supports professional computing and advanced manageability. With its innovative Low Power Active Mode feature and highly-efficient integrated power supply, this powerful mini PC ensures instant communication capabilities in your office while significantly reducing power bills. The optional Palm vein authentication combined with PalmSecure™ technology provides unrivaled security. With its halogen-free printed circuit board of mainboard and optional PVC-free power cord, it is an example of the Fujitsu commitment to environmental protection and sustainability. Experience a cleaner, quieter workplace with Zero Noise PC function and the small footprint of the FUJITSU ESPRIMO Q958.



#### An elegant mini PC for standard office applications

Eye-catching exclusive modern design

- Fully equipped PC with a volume of ~2.0 liters - based on standard desktop technology

#### Zero Noise PC

Pleasant working environment due to completely quiet system (solid state disk required)

- Fan stop in standard operations

#### Superb usability

Efficient working environment due to a tidy desk with easy access to front connectors

- Horizontal or vertical operations and an integrated VESA mount, easy upgrade of major components

#### Feature-rich, energy-efficient mini PC based on green technology

Be ready for instant communication and a significantly reduced energy bill

- Innovative Low Power Active Mode and energy-efficient integrated power supply
- Halogen-free printed circuit board of mainboard, optional PVC-free power cord

#### State-of-the-art security features

Keep your most valuable assets safe - your data

- Workplace Protect (secure authentication solution), Trusted Platform Module (TPM) 2.0, optional palm vein sensor for PalmSecure™ technology, SmartCard reader, EraseDisk



# Components

| <b>Operating systems</b>              |   |
|---------------------------------------|---|
| <b>Operating system pre-installed</b> | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home   |
| <b>Operating system notes</b>         | Certified for SUSE Enterprise Desktop<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .  |
| <b>Processor</b>                      | Intel® Core™ i7-8700T processor (6 Cores / 12 Threads, 2.40 GHz, up to 4.0 GHz, 12 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8500T processor (6 Cores / 6 Threads, 2.10 GHz, up to 3.5 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i3-8100T processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® UHD Graphics 630)<br>Intel® Core™ i5-9500T processor (6 Cores / 6 Threads, 2.20 GHz, up to 3.7 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, 9 MB, Intel® UHD Graphics 630)<br>Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) *<br>Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)<br>Intel® Pentium® Gold G5420 (2 Cores / 4 Threads, 3.80 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610)<br><br>Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors<br>*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) |
| <b>Memory modules</b>                 | 4 GB (1 module(s) 4 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM<br>8 GB (1 module(s) 8 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM<br>16 GB (1 module(s) 16 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM  |
| <b>Hard disk drives (internal)</b>    | SSD PCIe, 1024 GB M.2 NVMe Highend module<br>SSD PCIe, 512 GB M.2 NVMe Highend module<br>SSD PCIe, 256 GB M.2 NVMe Highend module<br>SSD PCIe, 1024 GB M.2 NVMe module<br>SSD PCIe, 512 GB M.2 NVMe module<br>SSD PCIe, 256 GB M.2 NVMe module<br>SSD PCIe, 1024 GB M.2 NVMe module, SED<br>SSD PCIe, 512 GB M.2 NVMe module, SED<br>SSD PCIe, 256 GB M.2 NVMe module, SED<br>SSD SATA III, 1024 GB, 2.5-inch<br>SSD SATA III, 512 GB, 2.5-inch<br>SSD SATA III, 256 GB, 2.5-inch<br>SSD SATA III, 128 GB, 2.5-inch<br>HDD SATA III, 7,200 rpm, 500 GB, 2.5-inch<br>HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch*<br>HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch<br>Intel Optane Memory (16 GB)   |
| <b>Hard disk notes</b>                | SSD (Solid State Disk)<br>SED (Self-Encrypting Drive)   |
| <b>Graphics</b>                       | DP to DVI-D (single link) Adapter Cable   |
| <b>Drives (optional)</b>              | BD Triple Writer SATA ultra slim (tray)<br>DVD Super Multi ultra slim (tray)  |

**Interface add on cards/components  
(optional)**

|   |
|---|
| Serial Port   |
| M.2 WLAN 802.11ac (2x2) and BT 5 (dedicated regions only) |

## Base unit

|                                |   |
|--------------------------------|---|
| Base unit                      | ESPRIMO Q958  |
| <b>Mainboard</b>               |   |
| Mainboard type                 | D3613   |
| Formfactor                     | proprietary   |
| Chipset                        | Intel® Q370   |
| Processor socket               | LGA 1151  |
| Processor quantity maximum     | 1   |
| Supported capacity RAM (max.)  | 32 GB   |
| Memory slots                   | 2 DIMM (DDR4)   |
| Memory frequency               | 2,666 MT/s  |
| Memory notes                   | Dual channel support<br>For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor                          |
| LAN                            | 10/100/1,000 MBit/s Intel® I219LM   |
| Integrated WLAN                | 1 (optional with Bluetooth together)  |
| BIOS version                   | AMI Aptio V<br>UEFI Specification 2.6   |
| BIOS features                  | BIOS Flash EPROM update by software<br>Recovery BIOS<br>Unified Extensible Firmware Interface (UEFI)<br>Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology |
| Audio type                     | On board  |
| Audio codec                    | Realtek ALC671  |
| Audio features                 | Internal speaker supports audio playback (optional), High Definition audio  |
| <b>I/O controller on board</b> |   |
| Serial ATA total               | 2   |
| thereof SATA III               | 2   |
| Controller functions           | Serial ATA III (6 Gbit)<br>NCQ<br>AHCI  |
| <b>Interfaces</b>              |   |
| Audio: line-out                | 1   |
| Front audio: microphone        | 1   |
| Front audio: headphone         | 1   |
| USB 2.0 total                  | 2   |
| USB 3.1 Gen1 (USB 3.0) total   | 2   |
| USB 3.1 Gen2 total             | 5   |
| USB front                      | 2x USB 3.1 (Gen2); 1x USB 3.1 Type-C (Gen2)   |
| USB rear                       | 2x USB 2.0; 2x USB 3.1 (Gen1); 2x USB 3.1 (Gen2)  |
| VGA                            | optional: via external active adapter cable   |
| DisplayPort                    | 2   |
| DVI                            | 1 (DVI-D)   |

**Interfaces**

|                         |  |
|-------------------------|--|
| Serial (RS-232)         | optional: serial port (9pin, 16 byte FIFO, 16550 compatible)             |
| Mouse / Keyboard (PS/2) | 0/1 optional (with PC on/off function on Pin6)                           |
| Ethernet (RJ-45)        | 1  |
| Interface Module notes  | Anytime USB charge functionality, USB Typ C connector supports up to 15W |

**Input device / components**

|                          |  |
|--------------------------|--|
| Input devices (optional) | Keyboard<br>Mouse<br>KBPC PX ECO<br>Mouse M440 ECO |
|--------------------------|--|

**Drive bays**

|                         |   |
|-------------------------|---|
| Drive bays total        | 3   |
| 2.5-inch internal bays  | 1   |
| 5.25-inch external bays | 1   |
| M.2-2280                | 1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s; supports Intel® Optane™ technology) |

**Mini PCI slots**

|          |                              |
|----------|------------------------------|
| M.2-2230 | on mainboard for WLAN module |
|----------|------------------------------|

**Graphics on board**

|                              |   |
|------------------------------|---|
| Graphics brand name          | Intel® UHD Graphics 610, Intel® UHD Graphics 630  |
| Shared video memory          | Up to half size of total system memory  |
| TFT resolution (DVI)         | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel   |
| TFT resolution (DisplayPort) | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel<br>2,560 x 1,440 pixel<br>2,560 x 1,600 pixel<br>3,440 x 1,440 pixel<br>3,840 x 2,160 pixel<br>4,096 x 2,304 pixel  |
| Graphics features            | Support for up to three independent displays<br>DirectX® 12<br>HDCP support<br>OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors)<br>OpenGL® 4.5<br>DisplayPort interface supports Ver. 1.2 incl. Multi-Stream<br>DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included) |
| Graphics notes               | up to 1 GB dedicated video memory (main memory owned and locked for graphics use)<br>Tested resolutions, depending on display type additional resolutions and frequencies possible<br>Shared memory depending on main memory size and operating system<br>Resolution (color depth up to 32 Bit/pixel)<br>For TFT we recommend using 60Hz                    |

**Electrical values**

|                       |   |
|-----------------------|---|
| Power efficiency note | power supply efficiency (at 230V; 2 Watt/ 10% / 20% / 50% / 100% load) : > 85%/ 90% / 90% / 92% / 92% |
| Rated voltage range   | 100 V - 240 V   |
| Rated frequency range | 50 Hz - 60 Hz   |

**Electrical values**

|                                      |   |
|--------------------------------------|---|
| Operating voltage range              | 90 V - 264 V  |
| Operating line frequency range       | 47 Hz - 63 Hz   |
| Max. output of single power supply   | 65 W (integrated in system)                             |
| Power factor correction/active power | No (meets input harmonic current according EN61000-3-2) |

**Power consumption**

|                            |   |
|----------------------------|---|
| Power consumption note     | See white paper Energy Consumption  |
| Link to Energy White Paper | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=938eb419-360e-4ba2-9b7f-86fdded0d7a4">http://docs.ts.fujitsu.com/dl.aspx?id=938eb419-360e-4ba2-9b7f-86fdded0d7a4</a> |

**Heat dissipation**

|                        |                                    |
|------------------------|------------------------------------|
| Heat dissipation notes | See white paper Energy Consumption |
|------------------------|------------------------------------|

**Noise emission**

|  |   |
|--|---|
| Related Processors for noise                           | Intel® Core™ i7 8700T   |
| Standard noise emission                                | 2x4 GB, SSD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74  |
| Standard noise notes / description                     | A-weighted sound power level Lw <sub>d</sub> (in B) / Workplace related A-weighted sound pressure level Lp <sub>Am</sub> (in dB(A)) |
| Standard noise operation mode: CPU 50% load            | 3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position  |
| Standard noise operation mode: HDD load                | 3.0 B / 17 dB(A) Bystander; 16 dB(A) Operator position  |
| Standard noise operation mode: Idle mode               | 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position  |
| Standard noise operation mode: ODD load                | 4.4 B / 30 dB(A) Bystander; 34 dB(A) Operator position  |
| Standard noise operation mode: Office applications 2.0 | 3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position  |

**Dimensions / Weight / Environmental**

|                               |  |
|-------------------------------|--|
| Dimensions (W x D x H)        | 185 x 190 x 54 mm; with VESA cover: 185 x 190 x 56.2 mm<br>7.29 x 7.49 x 2.13 inch |
| Operating position            | Vertical / horizontal (no feet needed)   |
| VESA mount                    | optional VESA cover required   |
| Weight                        | 1.6 kg   |
| Weight (lbs)                  | 3.53 lbs   |
| Weight notes                  | Actual weight may vary depending on configuration                                  |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F)  |
| Operating relative humidity   | 5 - 85 % (relative humidity)   |

**Compliance**

|                  |   |
|------------------|---|
| Product          | ESPRIMO Q958  |
| Model            | MPC3  |
| Germany          | TÜV GS  |
| Europe           | CE  |
| USA/Canada       | FCC Class B<br>cTUVus   |
| Global           | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL)<br>ENERGY STAR® 7.1<br>EPEAT® Bronze (dedicated regions) |
| China            | CCC (planned)<br>CCC (depending on configuration)<br>CEL (Chinese energy label)<br>TPM 2.0 for China (optional)   |
| Compliance notes | This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord   |

**Compliance**

|                        |   |
|------------------------|---|
| <b>Compliance link</b> | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a> |
|------------------------|---|

**Additional Software**

|   |  |
|---|--|
| <b>Additional software (preinstalled)</b> | <p>Adobe® Reader® (pdf reader)</p> <p>McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed)</p> <p>Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)</p>  |
| <b>Additional software (optional)</b>     | <p>Recovery DVD for Windows®</p> <p>Drivers &amp; Utilities DVD (DUDVD)</p> <p>CyberLink PowerDVD BD (playback software for Blu-ray Disc™)</p> <p>CyberLink PowerDVD DVD (playback software for DVD)</p> <p>Nero Essentials XL</p> <p>Microsoft® Office Professional 2019</p> <p>Microsoft® Office Home and Business 2019</p> <p>(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)</p> |

**Manageability**

|                                 |   |
|---------------------------------|---|
| <b>Manageability technology</b> | <p>DeskUpdate Driver management</p> <p>PXE 2.1 Boot code</p> <p>Wake up from S5 (off mode)</p> <p>Intrusion switch (optional)</p> <p>WoL (Wake on LAN)</p> <p>iAMT 12.0 (depending on processor)</p>  |
| <b>Manageability software</b>   | <p>DeskView Client</p> <p>DeskView Instant BIOS Management</p>  |
| <b>DeskView components</b>      | <p>BIOS Management incl. Security</p> <p>Inventory Management</p> <p>Driver Management</p> <p>Alarm Management</p>  |
| <b>Supported standards</b>      | <p>DMI (Desktop Management Interface)</p> <p>SMBIOS (System Management BIOS)</p> <p>PXE (Preboot Execution Environment)</p> <p>WMI (Windows Management Instrumentation)</p> <p>WBEM (Web Based Enterprise Management)</p> <p>CIM (Common Information Model)</p> |
| <b>Manageability link</b>       | <a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>   |

**Security**

|                                 |   |
|---------------------------------|---|
| <b>Physical Security</b>        | <p>Kensington Lock support</p> <p>Eye for padlock</p> <p>Housing Lock Spring (to use with Kensington lock), (optional)</p>  |
| <b>System and BIOS Security</b> | <p>Embedded security (TPM 2.0)</p> <p>EraseDisk (optional)</p> <p>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME)</p> <p>Boot sector virus protection</p> <p>Write protect option for the Flash EPROM</p> <p>Control of all USB interfaces</p> <p>External USB ports can be disabled separately</p> <p>Control of external interfaces</p> |
| <b>User Security</b>            | <p>User and supervisor BIOS password</p> <p>Hard disk password</p> <p>Access protection via internal SmartCard reader (optional)</p> <p>Access protection via external SmartCard reader (optional)</p> <p>Embedded PalmSecure™ sensor (optional)</p> <p>Workplace Protect (secure authentication solution)</p>  |
| <b>Workplace Embedded Tools</b> | <p>Auto BIOS Update via Fujitsu Server</p> <p>Auto BIOS Update via customer server</p> <p>Easy PC Protection</p>  |

|   |  |
|---|--|
| <b>Security</b>   |  |
| <b>Security notes</b>                                   | Choose people over passwords. Protect your business with PalmSecure technology. <a href="http://choosepeopleoverpasswords.global.fujitsu.com/">http://choosepeopleoverpasswords.global.fujitsu.com/</a> #High accuracy: PalmSecure™ has a proven false rejection rate of 0.01 percent and a false acceptance rate of less than 0.00001 percent. No other system in the world can match this performance. #Hygienic and non-invasive: Contactless scanner #Easy to use: Scanning is intuitive and people feel no mental resistance to it.   |
| <b>Miscellaneous</b>                                    |  |
|   | Keyboard on (Special Fujitsu keyboard required)<br>Keyboard on with one key (KBPX Eco, KB521)<br>Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards<br>Keyboard on with any key (USB)<br>Thermal management<br>Low Power Active Mode<br>Extended lifetime   |
| <b>Accessories information</b>                          | Further helpful options<br><br>Desktop Accessories:<br><a href="http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/">http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/</a><br><a href="http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/">http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/</a><br><br>Stands and Mounting kits:<br><a href="http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html">http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html</a><br>Available Adapters: <a href="http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf">http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf</a> |
| <b>Serviceability</b>                                   |  |
|   | EasyChange for HDD<br>EasyChange for optical drives  |
| <b>Packaging information</b>                            |  |
| <b>Packaging dimension (mm)</b>                         | 395 x 198 x 284 mm   |
| <b>Packaging dimension (inch)</b>                       | 15.55 x 7.8 x 11.18 inch   |
| <b>Max. quantity / pallet</b>                           | 84   |
| <b>Material - Weight (g) Carton</b>                     | 670 g  |
| <b>Material - Weight (lbs) Carton</b>                   | 1.48 lbs   |
| <b>Material - Weight (g) EPS / PS</b>                   | 10 g   |
| <b>Material - Weight (lbs) EPS / PS</b>                 | 0.02 lbs   |
| <b>Material - Weight (g) PE</b>                         | 125 g  |
| <b>Material - Weight (lbs) PE</b>                       | 0.28 lbs   |
| <b>Packaging notes</b>                                  | If keyboard is included in packaging: 1.) packaging dimension is increasing to: 500 x 208 x 290mm / (19.69 x 8.19 x 11.42 inch); 2.) material weight of carton will increase to 880g; 3.) max. quantity/pallet = 56; printed user documentation is bleached in chlorin free process;   |
| <b>Warranty</b>   |  |
| <b>Warranty period</b>                                  | 3 years (depending on country)   |
| <b>Warranty type</b>                                    | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)   |
| <b>Warranty Terms &amp; Conditions</b>                  | <a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>  |
| <b>Product Support Services - the perfect extension</b> |  |
| <b>Recommended Service</b>                              | 9x5, Onsite Response Time: Next Business Day   |
| <b>Spare Parts availability</b>                         | 5 years after end of product life<br>5 years   |
| <b>Service Weblink</b>                                  | <a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>  |

## Recommended Accessories

**Mounting Kit for Height Adjustable FUJITSU Displays**

The FUJITSU Mounting Kit for Height Adjustable FUJITSU Displays has been specifically designed for use with ESPRIMO Q/G mini PCs, FUTRO Thin Clients and FUJITSU Displays. By mounting an ESPRIMO mini PC or a FUTRO Thin Client behind a display, you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:  
S26361-F2542-L452

**Display P27-8 TS UHD**

The FUJITSU Display P27-8 TS UHD has a 3840 x 2160 Ultra HD resolution ships with a thin bezel housing ideal for multi-monitor use scenarios. The monitor has a 178°/178° wide viewing angle that delivers consistent picture quality, a 100% sRGB color space, ECO function, DisplayView™ IT Suite manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:  
S26361-K1610-V160

**Display B34-9 UE**

The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:  
S26361-K1642-V140

**Display P24-8 WS Neo**

The FUJITSU Display P24-8 WS Neo is a 16:10 IPS panel monitor that has DisplayView™ IT Suite that helps you activate features such as Presence Sensor, Workplace Lighting Guide that promote the overall ergonomics and security of your workplace. The monitor has a 178°/178° wide viewing angle delivering a consistent picture quality and is ideal for CAD and Document Management applications.

Order Code:  
S26361-K1647-V160

**Wireless Mouse Touch WI910**

The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:  
S26381-K465-L100

**Keyboard KB950 Phone**

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4\*\* (\*\*:  
Country specific variation)



## More information

### Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO Q958, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about FUJITSU Desktop ESPRIMO Q958, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2019-08-01 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH